

NEW & IMPROVED

ENDURO-FLEX TURBO™

Fastest removal rate in the industry,
now with +25% more life



WALTER

Achieve Greatness™

ENDURO-FLEX TURBO™

Increase your productivity with the ENDURO-FLEX TURBO™ thanks to its unique 36/60 grit ceramic grain blend that removes material quickly and leaves a paint-ready finish. Now with MAX LIFE™ cold curing glue ensuring the freshest grains possible by eliminating the need to apply heat to the disc during the manufacturing process, improving consistency and maximizing disc life. The patented Turbofan™ design minimizes heat transfer to the surface further improving disc life. Compatible with both steel and stainless steel, ENDURO-FLEX TURBO™ helps you work better thanks to the fastest removal rate in the industry.



TYPE 27S

Dia.	Arbor	Order No.	Grade	Max. RPM	Std. Pkg.	Std. Ctn.
4 1/2"	5/8"-11	06-A 452	36/60	13,300	10	40
4 1/2"	5/8"-11 metal hub	06-A 457	36/60	13,300	10	40
4 1/2"	5/8"-11	06-A 458	80	13,300	10	40
5"	5/8"-11	06-A 502	36/60	12,200	10	40
5"	5/8"-11	06-A 508	80	12,200	10	40
6"	5/8"-11	06-A 602	36/60	10,200	10	40
7"	5/8"-11 metal hub	06-A 707	36/60	8,600	10	40

Always use with flange 30-B 057.



TYPE 27

Dia.	Arbor	Order No.	Grade	Max. RPM	Std. Pkg.	Std. Ctn.
4 1/2"	7/8"	06-A 462	36/60	13,300	10	40
5"	7/8"	06-A 512	36/60	12,200	10	40
7"	7/8"	06-A 712	36/60	8,600	10	40

Always use with flange 30-B 057.

NEW

With a more ergonomic angle of attack, the type 29 allows for a higher removal rate best suited for heavy-duty applications such as blending contours, edges and corners.



TYPE 29

Dia.	Arbor	Order No.	Grade	Max. RPM	Std. Pkg.	Std. Ctn.
4 1/2"	7/8"	06-A 482	36/60	13,300	10	40
4 1/2"	5/8"-11 metal hub	06-A 487	36/60	13,300	10	40
5"	7/8"	06-A 532	36/60	12,200	10	40
5"	5/8"-11 metal hub	06-A 537	36/60	12,200	10	40

FOR MORE INFORMATION, TO SCHEDULE A FREE DEMO OR TO ORDER:

United States:

Phone: (800) 522-0321 | Fax (866) 274-4435

Email: OrderDesk.US@walter.com

Canada:

Phone: (888) 592-5837 | Fax (866) 581-1121

Email: csr@walter.com



- ▷ Fastest removal rate in the industry
- ▷ MAX LIFE™ cold curing glue for longer life and consistent performance
- ▷ Patented Turbofan™ keeps the workpiece cooler for longer disc life
- ▷ Vibration-free and comfortable grinding



BEYOND THE GRAIN

WALTER's exclusive MAX LIFE™ cold curing glue ensures the freshest grains possible by eliminating the need to apply heat during the manufacturing process, avoiding micro-cracking and drying out, improving consistency and maximizing disc life.

Available at :

Walter Surface Technologies Inc. © 2023 All Rights Reserved. Walter Surface Technologies and Bio-Circle logos are trademarks or registered trademarks of Walter Surface Technologies Inc. Other company, product or service names may be trademarks or service marks of Walter Surface Technologies or others. 98-E 104 (11-23)