

COOLCUT S-30

Soluble Cutting Lubricant

Coolcut S-30 is a premium mineral oil based cutting fluid with EP additives designed for all metal removal applications in steel as well as non-ferrous metals. It is free of chlorinated compounds and nitrates. Mixing it with water results in a highly stable micro-emulsion with excellent lubricating and anti-corrosion properties. The emulsion resists bacteria growth and provides long bath life with little maintenance.

Features & Benefits:

- Dilutes up to 1:30
- Allows increased feed, speed and productivity
- Excellent corrosion protection
- Highly stable for long bath life
- Drilling, sawing, milling, turning, reaming, broaching, shaping, hobbing, grinding of ferrous and non-ferrous metals

Description	Size		Order No.	MSDS
	Metric	Imperial		
Liquid	5L	1.3 gal.	53-G 006	L-119E
Liquid	20L	5.2 gal.	53-G 007	L-119E
Liquid	208L	55 gal.	53-G 008	L-119E

ACCESSORIES

PB-30 Preservative Booster*	53-C 011
Valve for 5L containers	53-L 113
Valve for 20L container	53-L 207

**PB-30 Preservative Booster enhances the homogeneity of the emulsion, helps maintain pH levels and improves corrosion protection while eliminating odors.*

Technical Information

Refractometer Factor	0.9
Density	0.970 g/ml (at 20°C)
Flashpoint	N/A
Odor/color	Mineral oil like / Brown
pH (at 10%)	9.3
Rinsability	Fully miscible
Viscosity	570 mm ² /s (at 20°C)

MSDS available upon request or visit our web site at www.walter.com

COOLCUT S-30

Soluble Cutting Lubricant

Application dilution chart:

Material	Dilution ratio	Dilution %	Application
Steel and Cast iron	1:20 - 1:10	5% - 10%	Turning, Milling, Drilling, Threading, Tapping, Sawing, Reaming, Broaching, Shaping, Hobbing
Stainless Steel	1:14 - 1 :8	7% - 12%	Turning, Milling, Drilling, Threading, Tapping, Sawing, Reaming, Broaching, Shaping, Hobbing
Aluminum and Non-Ferrous Alloys	1:30 - 1:10	3,3% - 10%	Turning, Milling, Drilling, Threading, Tapping, Sawing, Reaming, Broaching, Shaping, Hobbing

Dilution Chart			
Dilution ratio	Dilution %	ml of cleaner/ 1L of water	fl. oz. of cleaner/ 1 gal of water
1:30	3,3%	33ml	4,3 fl. oz.
1:20	5%	50ml	6,4 fl. oz.
1:14	7%	70 ml	9,0 fl. Oz.
1:10	10%	100ml	12,8 fl. oz.
1:8	12%	120 ml	15,4 fl. oz.
1:7	15%	150 ml	19,2 fl. oz.

MSDS available upon request or visit our web site at www.walter.com