

SLAP SHOT™ PL

DESCRIPTION

Slap Shot™ PL is specially formulated to effectively dissolve and remove grease, oil and other contaminants where plastics and rubber-like compounds are present.

- Quick acting
- Penetrates and displaces moisture
- Effectively cuts through and removes grease, oil, paint, ink, glue, adhesive, wax, dirt and grime
- Fast evaporation
- Residue-free
- Safe on plastics and rubber-like compounds
- Free of chlorinated solvents, CFC and HCFC
- Strong jet blasts away contaminants

APPLICATIONS

Use Slap Shot™ PL for:

- Cleaning of metal parts in presence of plastic or gaskets
- Maintenance, repair and overhaul of motors, machinery, vehicles and equipment
- Removal of glue, paint, ink, resin, sealant and flux residue
- Cleaning of electric components, instruments, lenses, glass, chains, gears, cables, etc...

RECOMMENDATIONS FOR USE

- Spray directly on parts

TECHNICAL DATA

Physical state: Aerosol

Color: Colorless

Density: 0.701g/ml (20°C /68°F)

VOC: 99.9% (w/w)

Flash point: -60°C / -76°F

Engineering controls: Ensure adequate ventilation

Incompatible substances: Oxidizing agents

Storage: Store below 50°C /122°F

Shelf life: 2 years in closed container, stored in ideal conditions

ORDERING INFORMATION

Description	Size	Order No.	(M)SDS
Aerosol	400ml	53-C 552	L-64

(M)SDS available upon request or visit our web site at www.walter.com

Not for product specification. The technical data contained herein is intended as reference only and may change without notice