

ICECUT

DESCRIPTION

ICECUT cutting fluid is a superior quality cutting fluid made of a blend of high grade mineral and synthetic oils with EP additives. It is specially conceived to efficiently perform during drilling applications with annular cutters.

- Ready-to-use
- For steel, stainless steel, and other non-ferrous alloys
- Nitrate, amines and boron free
- Not WHMIS controlled

APPLICATIONS

ICECUT cutting fluid is suitable for applications such as:

- Drilling with annular cutters
- Drilling with carbide core cutters
- Other drilling operations

AN UNBEATABLE TRIO!

- 1- *Magnetic base drilling unit*
- 2- *ICECUT™ annular cutters*
- 3- *ICECUT cutting fluid*

RECOMMENDATIONS FOR USE

- Use as is, without diluting
- Pour in receptacle intended for this purpose on magnetic base drills or other drilling units used with annular cutters.

TECHNICAL DATA

Color: Blue liquid

pH: 9.2@20°C (68°F)

Flammability: No

Flashpoint: 150°C (302°F)

Boiling point: >100°C (212°F)

Freezing point: 0°C (32°F)

Specific gravity: 0.97 g/ml@20°C (68°F)

Water solubility: Soluble

Engineering controls: N/A

Incompatible substances: Strong oxidizers

Storage: Below 50°C (122°F)

Shelf life: 2 years in closed container, stored in ideal conditions

Transport : Not controlled for transportation

WHMIS: Not controlled

ORDERING INFORMATION

Description	Order No.	MSDS
5L	53-C 056	L-122
20L	53-C 057	L-122

ACCESSORIES

Valve for 5L	53-L 113
Valve for 20L	53-L 207