

E-WELD PLASMA

Long lasting protection for laser and plasma cutting tables

E-WELD PLASMA™ is a ceramic anti-spatter solution that is applied to laser and plasma cutting tables to reduce the buildup of slag over time. By using our ergonomic arm-mounted sprayer, you can quickly coat large surface areas. This simple preventative measure keeps the slag from adhering to the slats in cutting tables, allowing it to be easily removed before it builds up and becomes problematic. This significantly decreases the amount of time and effort needed to clean slag off cutting tables, which saves you a great deal of labor time – and associated costs – in plant maintenance.



Features & benefits:

- Ceramic formula provides long lasting protection, even in the presence of extreme heat
- Arm-mounted spray gun applicator allows you to quickly and easily dispense the product across large surface areas
- Each 10 kg container provides enough anti-spatter to cover at least 50 square meters (500 square feet)
- E-Weld Plasma can be painted on manually or sprayed on with the applicator; just stir the solution prior to use
- Use a degreaser like Surfox Pre-Weld to clean slats prior to use to ensure a strong, adhesive coating

Tips & tricks:

- Apply in thin coats
- Let dry for at least 4 hours. Maximum results after 12 hours
- For dry tables and semi-submerged tables only

| Description | Size | | Order No. | SDS |
|-------------|--------|----------|-----------|--------|
| | Metric | Imperial | | |
| Liquid | 10 kg | 22 lb | 53-F 605 | L-142E |

ACCESSORIES

E-Weld Plasma Sprayer 53-L 125

Technical Information

| | |
|-------------|------------|
| Density | 1.65 g/ml |
| Flashpoint | N/A |
| Color | White |
| pH | 7 to 8 |
| Rinsability | Excellent |
| VOC | 2.9% (w/w) |