

SHIELD PRO™

Heavy-Duty Industrial Corrosion Protection

SHIELD PRO™ is a high performance rust inhibitor that provides long term corrosion protection coating, suitable for inside and outside use.

Features & Benefits:

- Long-term indoor and outdoor corrosion protection
- Penetrates and displaces moisture
- Non-drying film
- Resists salt water
- Salt spray test – 168 hours, no rust
- Flash point: 30°C (86°F)
- NSF registered, category code H2, registration number 147193
- Ideal for the corrosion protection of metal parts, for indoor and outdoor storage, outdoor equipment and tools, oversea storage and shipments, cables, chains, pulleys, pump and hose assemblies, and many more maintenance and repair applications

Description	Size		Order No.	(M)SDS
	Metric	Imperial		
Liquid	3.78L	1 gal	53-H 255	L-170F
Liquid	20L	5.2 gal	53-H 257	L-170F
Liquid	208L	52.8 gal	53-H 258	L-170F

ASTM tests:

- B-117 Salt Spray Corrosion test
- D-877 Dielectric strength

Cleaning: Use a solvent (Walter Slap Shot™ 53-C 502)

Accessories:

Spout 20L/ 200L metal drum (3/4") 53-L 208
E-Weld sprayer 53-L 126

Technical Information

Density	0.99g/ml (20°C / 68°F)
Flashpoint	30°C /86°F
Odor/color	Characteristic, beige
Dielectric strength	5.52kv (semi-conductor)
Solubility in water	Immiscible with water
Viscosity	< 0.225cm ² /s (40°C / 104°F)

(M) SDS available upon request or visit our web site at www.walter.com

Not for product specification. The technical data contained herein is intended as reference only and may change without notice.