

SLAP SHOT™ PL

DESCRIPTION

Slap Shot™ PL is specially formulated to effectively dissolve and remove grease, oil and other contaminants where plastics and rubber-like compounds are present.

- Quick acting
- Penetrates and displaces moisture
- Effectively cuts through and removes grease, oil, paint, ink, glue, adhesive, wax, dirt and grime
- Fast evaporation
- Residue-free
- Safe on plastics and rubber-like compounds
- Free of chlorinated solvents, CFC and HCFC
- Strong jet blasts away contaminants

APPLICATIONS

Use Slap Shot™ PL for:

- Cleaning of metal parts in presence of plastic or gaskets
- Maintenance, repair and overhaul of motors, machinery, vehicles and equipment
- Removal of glue, paint, ink, resin, sealant and flux residue
- Cleaning of electric components, instruments, lenses, glass, chains, gears, cables, etc...

RECOMMENDATIONS FOR USE

- Spray directly on parts

TECHNICAL DATA

Physical state: Aerosol

Colour: Colourless

Density: 0.701g/ml (20°C /68°F)

VOC: 99.9% (w/w)

Flash point: -60°C / -76°F

Engineering controls: Ensure adequate ventilation

Incompatible substances: Oxidizing agents

Storage: Store below 50°C /122°F

Shelf life: 2 years in closed container, stored in ideal conditions

ORDERING INFORMATION

Description	Size	Order No.	(M)SDS
Aerosol	400ml	53-C 552	L-64

(M) SDS available upon request or visit our web site at www.walter.com

Not for product specification. The technical data contained herein is intended as reference only and may change without notice.

Walter Surface Technologies Inc.

5977 Trans-Canada Highway, Pointe-Claire, Quebec H9R 1C1

Tel: 1-800-592-5837 or (514)630-2800 / Fax: (514)630-2825