

EXCLUSIVE NARROW
CROWN DEPRESSED
CENTER CUT-OFF
WHEELS

Get more reach!

New

Increases performance of the
best wheels on the market
by **30%**

“Only the best”

 **WALTER**
Surface Technologies

New EXCLUSIVE Narrow Crown on 4½” and 5” depressed center thin cut-off wheels



This technology is now incorporated in all 4½” and 5” ZIPCUT, ZIP+, ZIP STAINLESS AND ZIP ALU cutting wheels, making these cutting “Only the Best”, in their category.

Exclusive patented technology allowing deeper cutting depth!

Increases the cutting depth of the blade for better reach and less friction when getting close to the workpiece.



Also equipped with a unique metal protective cladding (patented technology)



Prevents contact with the workpiece and therefore improves safety

NEW Geometry Extends wheels life by

30%



Ideal for flush cutting

ZIPCUT™

*Lowest cost per cut in the industry
less friction and faster cutting*

TYPE 27 



Dia.	Thickness	Arbor	Order No.	Grade	Max RPM	Std. Pkg.	Std. Ctn.
4 1/2"	3/64" (.045")	7/8"	11-T 142	A-60-ZIP	13,300	25	400
5"	3/64" (.045")	7/8"	11-T 152	A-60-ZIP	12,200	25	400



ZIPCUT™ SPIN-ON

*Quick and easy wheel change
for minimum downtime*

SPIN-ON TYPE 27S 



Dia.	Thickness	Arbor	Order No.	Grade	Max RPM	Std. Pkg.	Std. Ctn.
4 1/2"	3/64" (.045")	5/8"-11	11-T 342	A-60-ZIP	13,300	25	400
5"	3/64" (.045")	5/8"-11	11-T 352	A-60-ZIP	12,200	25	400



ZIP ONE™

Extra thin for ultra precision cutting

TYPE 27 



Dia.	Thickness	Arbor	Order No.	Grade	Max. RPM	Std. Pkg.	Std. Ctn.
4 1/2"	1/32" (.032")	7/8"	11-T 642	ZA-60-ZIP	13,300	25	400
5"	1/32" (.032")	7/8"	11-T 652	ZA-60-ZIP	12,200	25	400



ZIP+™

Choose ZIP+ for the toughest projects

TYPE 27 



Dia.	Thickness	Arbor	Order No.	Grade	Max RPM	Std. Pkg.	Std. Ctn.
4 1/2"	1/16" (.062")	7/8"	11-T 453	A-46-ZIP	13,300	25	400
5"	1/16" (.062")	7/8"	11-T 503	A-46-ZIP	12,200	25	400





ZIP STAINLESS™

Superior cutting of nickel alloyed steels - guaranteed not to contaminate stainless steel



Fe-S-CI
<0.1%



TYPE 27

Dia.	Thickness	Arbor	Order No.	Grade	Max RPM	Std. Pkg.	Std. Ctn.
4 1/2"	3/64" (.045")	7/8"	11-F 142	A-60-SS-ZIP	13,300	25	400
5"	3/64" (.045")	7/8"	11-F 152	A-60-SS-ZIP	12,200	25	400



ZIP ALU™

Fast and free cutting of aluminum without clogging



TYPE 27

Dia.	Thickness	Arbor	Order No.	Grade	Max RPM	Std. Pkg.	Std. Ctn.
4 1/2"	3/64" (.045")	7/8"	11-U 142	A-60-SS-ALU	13,300	25	400
5"	3/64" (.045")	7/8"	11-U 152	A-60-SS-ALU	12,200	25	400

Tech tip!

Use the thick backing flange for a flush fit and minimal exposure of spindle beyond the clamping nut



For Walter grinder with:

5/8"-11 spindles Order No. 30-B 017

M14x2.0 spindles Order No. 30-B 016



Contact us today to meet with a Representative for a product demonstration

1-888-592-5837

WALTER.COM

Available at: